



SPECIFICATIONS for CRP-IDC Paks

		CRP- IDC Paks W/ Internal Decompression Chamber					
		CRP-7.5-IDC	CRP-15-IDC	CRP-30-IDC	CRP-55-IDC		
	INLETS (5) brass h.b.	.25"	.25"	.25"	.25"		
	OUTLET (1) poly barb	.5"	.5"	.5"	.5"		
	HEIGHT	20"	20"	29"	33"		
	WIDTH/DEPTH	15"	15"	19"	23"		
	MAX FLOW (GPM)	2	2	4	6		
	MAX TEMP (F)	125	125	125	125		
	SHIPPING WEIGHT	75#	110#	220#	400#		
	CRP-IDC PAK - PARTS LIST						
	CRP PAK	1					
Outlet Assembly	1						
Inlet Hub	1						
Drain Hose	1						

APPLICATION CHART FOR CRP-IDC UNITS

CRP-IDC Sizing Chart – based on compressor operating hours.

HORSE POWER	CRP-7.5-IDC	CRP-15-IDC	CRP-30-IDC	CRP-55-IDC
	OPERATING HOURS	OPERATING HOURS	OPERATING HOURS	OPERATING HOURS
5	52400	104800	Life spans may vary due to differences in air compressor oil consumption rates, age & maintenance of compressor.	
10	26000	52000		
15	17500	35000		
20	13000	26000		
25	10500	21000		
30	9000	18000		
35		15000		
40		11000		
50		10500	21000	37000
60		8500	18000	31000
75		7000	15000	26500
100		5000	10500	19000
150		3500	7000	12500
200		2500	5000	9500
300		1700	3500	6500
400			2500	5000
500			2100	3800
600			1700	3200